



**INDUSTRIAL
CHOICE**



INDUSTRIAL CHOICE SUPERDRAG DISCHARGE HOSE

**Thick Orange Urethane Tube & Covered, extruded thru the weave process,
High Pull/Tensile Strength Discharge Hose**



Lightweight: Easy to Handle-Move

Super Durable: Tough Polyurethane Cover

Ozone Resistant

Strong: High WP/Tensile/Pull Strength.



**Applications: Drag-Traveler-Linear-Fracking Hose: for Manure Transfer,
Water Discharge, Light Water based Fertilizers, Chemicals, Chlorine, Oils
Alkalizes, Brine, Glycols.**

See Chemical Chart -40F to 150F. High Tensile Pull Strength

Item	ID	Wall	WPSI	BPSI	Tensile	Weight	Notes
Number	(Inch	Thic			Strength	(lbs./ft.)	
SUPERDRAG-5	5"	0.157	200	600	41,110lbs	1.120	
SUPERDRAG-5.5	5.5"	0.157	150	600	43,616lbs	1.200	
SUPERDRAG-6	6"	0.157	200	600	49,985lbs	0.128	
SUPERDRAG-8	8"	0.118	150	450	76,796lbs	1.810	

Note! Dimensions, Weights can vary slightly & are approximate.

Wpsi is figured at 78deg F.

**Warning! Ends attached with bands, clamps or sleeves rated for under Wpsi of hose
will lower the overall Wpsi of the hose assembly.**

Tube: Thermoplastic-Poly-Urethane

Cover: Thermoplastic-Poly-Urethane

Reinforcement: Heavy 2 Ply High Tensile Strength Polyester Spirals

Temperature Range: -40F to +150F

Branded: Industrial Choice SuperDrag Discharge Hose 200-150 W.P.