





S113-S115 by Pacific Echo for Industrial Choice

Standard Duty PVC Water-Light Chemical Suction-Discharge Hose





<u>Applications:</u> Water, Light water based chemicals, Liquid Fertilizers, Drain Lines, Septic tank pumper hose-Porta-potty hose-Fish suction (clear) Rental and Construction dewatering, Air Seeder Line Etc.

rtomai and constitution demats mig, 7th coods. Eme Etc.								
ltem	ID	OD	Bend	WP	VAC	Burst	Weight	
<u>Number</u>	(Inch)	(Inch)	Radius	<u>(PSI)</u>	(HG)	(PSI)	(lbs/ft)	Notes:
S113/S115-3/4	0.75"	1.02"	2"	100	28.0	300	0.21	
S113/S115-1	1"	1.29"	3"	90	28.0	270	0.29	
S113/S115-1.25	1.25"	1.53"	4"	90	28.0	270	0.38	
S113/S115-1.5	1.5"	1.84"	4"	90	28.0	270	0.49	
S113/S115-2	2"	2.39"	5"	70	28.0	210	0.71	
S113/S115-2.5	2.5"	2.92"	7"	65	28.0	195	0.98	
S113/S115-3	3"	3.46"	8"	55	28.0	165	1.28	
S113/S115-4	4"	4.56"	12"	45	28.0	135	2.02	
S113/S115-5	5"	5.65"	18"	45	28.0	135	2.97	
S113/S115-6	6"	6.80"	20"	45	28.0	135	4.39	
S113/S115-8	8"	8.95"	34"	40	28.0	120	6.79	

Construction: Clear P'with Rigid White Helical Temperature Service Range: Deg.5F to 150F

Warning: The user of this product is responsible for determining if the hose is suitable for the application!

Note! WPSI & Bend Radius are calculated at 70deg F. As Temperatures go up WPSI goes down & bend radius increases. Approx. a 10deg increase = -10% wpsi & bend radius +10%.