



INDUSTRIAL CHOICE



GatorGlide EPDM Rubber/PVC Hose

Proprietary All Weather PVC Blended Helical-Smooth Rubber Inner Tube



Applications: Water-Light water based chemicals; Fertilizers-Herbicides-Septic Tank Pumper Hose-Porta-Potty Hose-Water Suction-Liquid Manure-Marine Bilge Discharge Etc.

Item Number	ID (Inch)	OD (Inch)	Bend Radius	WP (PSI)	Burst (PSI)	Weight (lbs/ft)	Notes
<u>GatorGlide-Epdm-AW-3/4</u>	3/4"	1.28	1.8	100	300	0.20	
<u>GatorGlide-Epdm-AW-1</u>	1"	1.37	1.9	90	270	0.25	
<u>GatorGlide-Epdm-AW-1.25</u>	1-1/4"	1.67	3.1	75	225	0.32	
<u>GatorGlide-Epdm-AW-1.5</u>	1-1/2"	1.97	3.2	70	210	0.52	
<u>GatorGlide-Epdm-AW-2</u>	2"	2.54	5.1	65	195	0.71	
<u>GatorGlide-Epdm-AW-3</u>	3"	3.65	7.0	55	165	1.24	
<u>GatorGlide-Epdm-AW-4</u>	4"	4.74	11.0	45	135	1.91	
<u>GatorGlide-Epdm-AW-6</u>	6"	6.90	20.0	35	105	3.90	

Note! Dimensions, weights can vary slightly & are approximate! WPSI is based on Temp @ 70deg F.

Tube: Black EPDM Thermo Rubber through out the length of the hose, no exposed Helical.

Cover: Green Raised Special blended PVC Helical is very flexible and very Durable.

Temperature Ranges: Deg.-40F to 140F

Warning: The user of this product is responsible for determining if the hose is suitable for the application!

Note! WPSI & Bend Radius are calculated at 70deg F. As Temperatures go up WPSI goes down & bend radius increases. Approx. a 10deg increase = -10% wpsi & bend radius +10%.

Compare to: KANAFLEX 300EPDM, KURIYAMA Tiger Green, Pacific Echo S2006.